




Compact Urine Analyzer

PocketChem™ UA

PU-4010



It's lightweight, small and mobile

Compact Urine Analyzer

Pocketchem™ UA

PU-4010



Multiple functions

Colored urine compensation, ambient temperatures compensation and Specific Gravity compensation by pH.

Palm-sized meter driven by two batteries

The meter is detachable from the printer. The meter is really portable and mobile. It may go easily near patients.

Easy operation and daily maintenance

Just press the start key, dip and place the strip on the meter. For daily maintenance, clean the strip holder only.

Highly reliable test results with Creatinine compensation

Even with the use of spot urine, test results are highly reliable without influences by urine dilutions or concentrations. P/C ratio or A/C ratio is effective for renal diseases screening.

Meter Specification

Sample	Urine
Test strip	AUTION Sticks (4EA~10EA, 10PA), AUTION SCREEN
Measurement items	Glu, Pro, Bil, Uro, S.G, Bld, pH, Ket, Nit, Leu Cre and Alb
Measurement Principle	Dual wavelength reflectance method
Sample supply	Manual dipping
Measurement capacity	50 tests per hour
Reaction time	60 seconds per test
Display	Custom liquid crystal display
Memory capacity	100 tests
External output	RS-232C
Environment	Temperature : 10-30°C. Humidity : 20-80% RH(non-condensing)
Dimensions	124(W) × 81(D) × 36(H)mm
Weight	180g (without batteries)
Power supply	AA Alkaline battery × 2 or AC adapter
Power consumption	3W

Printer specification

Printer	Thermal line printer
Recording paper	Thermal paper 58mm(W) × φ26mm
Dimensions	125(W) × 133(D) × 36(H)mm
Weight	180g (without paper)
Power supply	AC adapter
Power consumption	20W
Connection with meter	One touch connection (with easy lock function)

※Design and specifications may be changed without prior notice

ARKRAY GLOBAL BUSINESS, INC.

KYOTO MIYUKI Bldg. 10F, 689 Takanna-cho,
Nakagyo-ku, Kyoto 604-8153, JAPAN

TEL +81-75-662-8967 FAX +81-75-662-8973

